



EUROPEAN COMMISSION
DIRECTORATE-GENERAL III
INDUSTRY
Industrial affairs II: Capital goods industries
Construction

Brussels, 6 July 1998

M 121

MANDATE TO CEN/CENELEC
CONCERNING THE EXECUTION OF STANDARDISATION WORK
FOR HARMONIZED STANDARDS ON

INTERNAL AND EXTERNAL WALL AND CEILING FINISHES

RELATED TO THE FOLLOWING END USES

04/33 EXTERNAL WALLS (INCLUDING CLADDING), INTERNAL WALLS AND PARTITIONS
10/33 SUSPENDED CEILINGS
11/33 EXTERNAL FINISHES OF WALLS
12/33 INTERNAL FINISHES OF WALLS AND PARTITIONS
14/33 CEILING FINISHES

FOREWORD

This mandate is issued by the Commission to CEN/CENELEC within the context of the Council Directive of 21 December, 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to construction products (89/106/EEC), hereafter referred to as "the Directive" or "the CPD".

One of the aims of the Directive being the removal of technical barriers to trade in the construction field, in so far as they cannot be removed by means of mutual recognition among Member States, it seems appropriate that standardisation mandates cover, at least during a first phase of the mandating programme, construction products likely to be subject to technical barriers to trade.

This mandate is intended to lay down provisions for the development and the quality of harmonised European standards in order, on the one hand, to make "approximation" of national laws, regulations and administrative provisions (hereafter referred to as "regulations") possible and, on the other hand, to allow products conforming to them to be presumed to be fit for their intended use, as defined in the Directive.

In this respect, this mandate takes account of the basic principles prevailing in the regulations of Member States, particularly those described in chapters 3 and 4.2 of the Interpretative documents, to which standardisers must refer. As stated by the Directive, the responsibility Member States have for construction works on their territory remains unchanged.

In order to fulfil the provisions of article 7.1 of the CPD the present mandate has been structured in the following way:

Chapter I Grounds. General conditions within the framework of the CPD.

Chapter II Execution of the mandate. Conditions regarding the programming, development and execution of the standardisation work.

CHAPTER I. GROUNDS

1. This mandate falls within the framework of the general policy of the Commission with respect to technical harmonisation and standardisation, as well as within the scope of the Directive. It replaces any previous mandate on the same products formerly issued on a provisional base by the Commission.

2. This mandate is based on article 7 of the Directive and has taken into consideration the Interpretative Documents⁽¹⁾ that serve as reference for the establishment of the harmonised standards (see article 12 of the Directive). It serves to ensure the quality of the harmonised standards for products, always with reference to the state of the art, with particular reference to the fitness of the products listed in annex 1 intended to be used in **EXTERNAL WALLS (INCLUDING CLADDING), INTERNAL WALLS AND PARTITIONS; SUSPENDED CEILINGS; EXTERNAL FINISHES OF WALLS; INTERNAL FINISHES OF WALLS AND PARTITIONS; and CEILING FINISHES**, enabling the works to satisfy the essential requirements set out in annex 1 of the Directive, provided that barriers to trade in these products exist and that the products fall within the scope of article 2.1 of the Directive;

3. Levels or classes of requirements for the works are under the responsibility of Member States and are not covered by the present mandate. As a consequence, they are not expected to be defined in the harmonised standard.

4. Levels or classes of requirements for the products may be determined either in the Interpretative Documents or according to the procedure provided for in article 20 (2) of the Directive. In either case, where levels or classes of requirements for products are determined, guidance is given in Annex 3 to this mandate. This is not the case for classes of convenience, which are classes of product performances developed as a means of convenience for specifiers, manufacturers and purchasers. Such classes of convenience are not covered by the present mandate and should not be defined within the harmonised standard. Nevertheless, the results of the determination of the product characteristics may be expressed using classes of convenience introduced by European standards. Articles 3.2 and 6.3 of CPD do not apply to such classes.

5. The harmonised standards resulting from this mandate must allow for products to comply with them even where performance does not need to be determined for a certain characteristic because at least one Member State has no legal requirement at all for such characteristic. Declaration of performance for such a characteristic, in this case, must not be imposed on the manufacturer if he does not wish to declare it.

6. Indications regarding the documents which should be taken into account to inform standardisers and manufacturers on national and harmonised legislation on substances classified as dangerous are given in Annex 4.

(1) O.J N°C 62, 28.02.1994

CHAPTER II. EXECUTION OF THE MANDATE

1. CEN/CENELEC will present the Commission with a detailed work programme, at the latest, **three months after acceptance by the 83/189 Committee**
2. The work programme should identify clearly the list of harmonised standards to be developed. For each harmonised standard it should:
 - a) indicate the name(s) of the product(s) to be covered;
 - b) define the characteristics, durability aspects, intended uses and the forms and materials to be covered (in accordance with Annexes 1, 2 and 3 of this mandate);
 - c) attach the list of supporting documents (e.g. work items on test methods, ...);
 - d) justify the timetable foreseen for its finalization; and
 - e) identify the Technical Committee(s) responsible for the work.
3. Clear differentiation should be made between the item to become the harmonised standard for the product and the items to be used as supporting documents.
4. When a supporting test standard for one characteristic does not exist or is not in the work programme of the TC, a clear statement should be presented indicating whether CEN is able to produce one or not.
5. Any proposals for the addition of products, intended uses and materials and forms not included in the mandate but considered relevant by the TC should be presented separately from the work programme for further analysis by the Commission services. Standards prepared for products outside this mandate will not achieve the status of harmonised standards. In addition to the provisions of article 4.1 of the CPD, it must be taken into account that all the products included in the mandate have a system of attestation of conformity in accordance with the relevant Decision of the Commission; those products not included have not.
6. Any proposal for the addition of characteristics and durability aspects not included in the mandate but considered relevant by the TC should be proposed in a special chapter of the work programme for further analysis by the Commission services.
7. Where a classification system of the product performances is envisaged in Annex 3 of the present mandate, CEN/CENELEC are requested to make an appropriate proposal for its implementation.
8. CEN/TCs must give a technical answer for the determination of the characteristics of the mandate taking into account the conditions stated below; test methods suggested must be directly related to the relevant required characteristic and must not make reference to determination methods for characteristics not required by the mandate. Durability requirements should be dealt with in the framework provided by the state of the art at present.
9. Reference to test/calculation methods must be in accordance with the harmonisation aimed at. In general, only one method should be referred to for the determination of each characteristic, for a given product or family of products.

If, however, for a product or family of products because of justifiable reasons, more than one method is to be referred to for the determination of the same characteristic, the situation must be justified. In this case all referenced methods should be linked by the conjunction "or" and an indication of application should be given.

In any other case, two or more test/calculation methods for the determination of one characteristic can be accepted only if a correlation between them exists or can be developed. The relevant harmonised product standard must then select one of them as the method of reference.

Testing and/or calculation methods shall have, whenever possible, a horizontal character covering the widest possible range of products

10. Within the work programme, CEN/CENELEC will also specify those cases where the performance-based approach will not be followed in the harmonised standard and will give the relevant justification.

11. After examination of the work programme and consultations with CEN/CENELEC, the Commission services will endorse the timetable and the list of standards or parts of standards which meet the terms of this mandate and which will be recognised as harmonised or supporting standards.

12. The terms of reference of this mandate may be subject to modification or addition, if necessary. Acceptance of the work programme by the Commission services does not imply acceptance of all the WIs listed as supporting standards. TCs will need to demonstrate the direct link between WIs and the needs for harmonisation of the products, intended uses and characteristics given in the mandate. Nor does acceptance exclude the possibility for further WIs to be added by CEN, in order to fully respond to the terms of the mandate

13. Representatives of the authorities responsible for national regulations have the right and shall be able to participate in the activities of CEN/CENELEC through their national delegations and to present their points of view at all stages of the drafting process of the harmonised standards.

14. The Commission may participate in standardisation activities as observer and has the right to receive all relevant documents.

15. CEN/CENELEC will immediately inform the Commission of any problem relating to the carrying out of the mandate and will present an annual progress report on work within the framework of the mandate.

16. The progress report will include a description of work carried out and information on any difficulties being met, whether political or technical, with particular reference to those that might lead the authorities of a Member State to raise objections or to resort to article 5.1 of the Directive.

17. The progress report will be accompanied by the latest drafts of each standard under the mandate and by updated reports on any subcontracted work.

18. Acceptance of this mandate by CEN/CENELEC will initiate the standstill procedure referred to in article 7 of Council Directive 83/189/EEC of 28 March 1983 modified by Council Directive 88/182/EEC of 22 March 1988 and the European Parliament and the Council Directive 94/10/EC of 23 March 1994.

19. Acceptance of this mandate by CEN/CENELEC can take place only after the work programme has been endorsed by the Commission services.

20. CEN/CENELEC will develop the draft harmonised European standards and of the relevant supporting standards on the basis of the work programme and will inform the Commission in good time that the draft is being circulated for public comment.

21. CEN/CENELEC will present the final drafts of the harmonised European standards and of the relevant supporting standards to the Commission services for confirmation of compliance with this mandate at the latest in accordance with the timetable agreed between CEN/CENELEC and the Commission and referred to in point II.2.d).

22. CEN/CENELEC members will publish the standards transposing the harmonised European standards at the latest 6 months after a positive vote in CEN/CENELEC. National standards covering the same scope will continue to be applicable until the date agreed between CEN/CENELEC and the Commission in accordance with point II.2.d)

CHAPTER III. HARMONISED STANDARDS

1. Harmonised standards shall be prepared to allow those products listed in Annexes 1 and 2 to be able to demonstrate the satisfaction of the essential requirements. One of the purposes of the Directive being to remove barriers to trade, the standards deriving from it will therefore be expressed, as far as practicable in product performance terms (art. 7.2 of the Directive), having regard to the Interpretative Documents.

2. The harmonised standard will contain:

- A detailed scope and field of application
- A detailed description of the product or family of products covered and the relevant intended uses of the different products;
- The definition of the characteristics of the products listed in Annex 2 of the mandate (expressed in performance terms, as far as practicable) that are relevant to the satisfaction of the essential requirements;
- The methods (calculation, test methods or others) or a reference to a standard containing the methods for the determination of such characteristics;
- Guidance on the characteristics that have to be stated within the labelling that will accompany the CE marking (depending on the intended use of the product) and on the way of expressing the determined values of these characteristics;
- The classification system and the levels for the above values of characteristics, if required by the mandate;
- The system for attestation of conformity as required in annex 3 of the mandate and the corresponding specific provisions for the evaluation of conformity.

3. A minimum or a maximum level of a given characteristic that has to be met by the family of products or a product may be identified by the harmonised standard only if required by agreement of Member States expressed by positive vote under the procedure of article 20 .

4. As far as possible, each standard will make reference to performances common to other standards developed under mandate and which constitutes a cohesive and compatible group of harmonised European standards developed in parallel. CEN/CENELEC shall ensure consistency within the whole package.

5. A producer not wishing to meet a non-mandated European standard will be able to use the CE marking on his product by referring only to the relevant harmonised standard. On the other hand, if a non-mandated standard includes the entire content of the harmonised standard, compliance with the former standard will also give a presumption of conformity to the harmonised standard and will enable the bearing of the CE marking.

In the latter case, an appropriate system should be established in the European standard in order to clearly distinguish the CPD-related content from the remaining part of the standard.

6. Harmonised standards must permit construction products which allow works to meet the essential requirements and which are produced and used lawfully in accordance with technical traditions warranted by local climatological and other conditions to continue to be placed on the market.

7. The essential requirements being expressed in terms of performance of the works, the characteristics of the products should be also expressed in terms of performance so that, in referring to the harmonised European standards, the regulations may "approximate" evolving in terms of "performance requirements". As far as practicable and depending on the intended use mentioned in the annexes of this mandate, the standard shall include a definition of the durability in term of performance of the declared values of the product characteristics as well as suitable methods for its evaluation against the actions listed in Annex 2. If the durability is expressed in terms of classes of periods, articles 3.2 and 6.3 of the CPD will not apply.

8. The relevant systems for attestation of conformity, according to Article 13.3 and Annex III of the Directive, are listed in annex 3. For the establishment of the corresponding specific provisions of evaluations of conformity, the harmonised standard will take into account:

- the different intended uses of the product mentioned in the annexes of this mandate and, if any, the different levels or classes of performance;
- cases of individual (non series) production according to Article 13.5 of the Directive;
- the recommendations of paragraph 3 of Annex 3

9. The label accompanying the CE marking will list all the characteristics to be declared according to the declared intended uses mentioned in the annexes of this mandate. In order to take into account existing regulations on products where performance for one or more characteristics may not be required, the label should allow the manufacturer the application of the "No performance determined" case for that or those characteristics.

ANNEX 1
FIELD OF APPLICATION

INTERNAL AND EXTERNAL WALL AND CEILING FINISHES

LIST OF PRODUCTS TO BE INCLUDED IN THE MANDATE TO BE USED IN:

04/33 EXTERNAL WALLS (INCLUDING CLADDING), INTERNAL WALLS AND PARTITIONS

10/33 SUSPENDED CEILINGS

11/33 EXTERNAL FINISHES OF WALLS

12/33 INTERNAL FINISHES OF WALLS PARTITIONS

14/33 CEILING FINISHES

For the purpose of this mandate, finishes are those products (simple or composite) intended to become the external layer of a wall or a ceiling.

FORM	MATERIALS	PRODUCTS FOR CONSIDERATION
Flexible sheets/rolls	organic fibres paper inorganic fibres rubber plastics composites cork	wall coverings in roll form ceiling linings
Rigid sheets (small and medium size)	natural stone cast stone concrete clay ceramic metal timber plastics, including foamed bituminous surface treated mineral wool wood wool organic fibres inorganic fibres fibre reinforced calcium silicate fibre cement slates	cladding slabs , with or without integrated fixation shingles (overlapping tiling) wall tiles (buted tiling) ceiling tiles
Rigid sheets (large size)	metal reinforced concrete fibre cement timber plastics cork inorganic boards composites	wall panels , including large metallic claddings, high/low pressure laminates and sandwich panels with or without insulation ceiling panels , including sandwich panels with or without insulation <i>(except those panels already covered by previous mandates to CEN - gypsum and wood-based - and EOTA - internal partition kits)</i>

Cont.

FORM	MATERIALS	PRODUCTS FOR CONSIDERATION
Profiles	timber metal plastics composites fibre cement wood based materials	sidings
Components, Sections	metals ^(*) timber ^(*) plastics	featured profiles suspending frames (<i>for suspended ceilings</i>)
kits including: e.g. rigid sheets and components/sections	(as above) (as above) (as above)	suspended ceilings (kits) , including ceiling tiles or ceiling panels and suspended frames

^(*) Products made of these materials are not covered by this mandate since they are in the mandate for structural metallic sections and for structural timber products.

ANNEX 2

TECHNICAL TERMS OF REFERENCE

Note : not all of the characteristics shown in the following tables will be relevant for every product in a particular family or sub-family. CEN/CENELEC should select the subset of characteristics applicable to a particular product from the full set provided. The brackets after characteristics provide guidance, but should be carefully checked.

INTERNAL AND EXTERNAL WALL AND CEILING FINISHES
--

TO BE USED IN:

04/33 EXTERNAL WALLS (INCLUDING CLADDING), INTERNAL WALLS AND PARTITIONS
 10/33 SUSPENDED CEILINGS
 11/33 EXTERNAL FINISHES OF WALLS
 12/33 INTERNAL FINISHES OF WALLS AND PARTITIONS
 14/33 CEILING FINISHES

Family

INTERNAL FINISHES

Family and subfamilies

1.- WALL COVERINGS IN ROLL FORM Including heavy duty, self finished or for subsequent decoration.

2.-CEILING LININGS Including heavy duty, self finished or for subsequent decoration.
--

Characteristics of WALL COVERINGS IN ROLL FORMS AND CEILING LININGS FOR INTERNAL USES to be covered by the harmonised standard will be:

E R	PERFORMANCE CHARACTERISTIC	Durability
1		Y
2	Reaction to fire (only for coverings/linings intended for uses on walls/ceilings subject to reaction to fire regulations)	
3	Release formaldehyde (where relevant, according to material) Release of pentachlorophenol (where relevant, according to material) Release of other dangerous substances * (as relevant) Susceptibility to the growth of harmful micro-organisms Water vapour permeability (only for coverings/linings intended for use on walls/ceilings subject to water vapour control requirements) Water permeability (only for coverings/linings intended for uses on walls/ceilings subject to water penetration requirements)	
4		
5		
6	Thermal resistance (only for coverings/linings intended for uses in walls/ceilings subject to thermal insulation requirements)	

* in particular, those dangerous substances defined in Council Directive 76/769/EEC, as amended.

Family and subfamilies

3.- WALL AND CEILING TILES

Elements of regular geometric forms with reduced thickness and such dimensions that can be easily held by one person. To be adhered or mechanically fixed to wall or ceiling or suspended to ceiling.

Characteristics of the WALL AND CEILING TILES FOR INTERNAL USES to be covered by the harmonised standard will be:

E R	PERFORMANCE CHARACTERISTIC	Durability
1		Y
2	Reaction to fire (only for tiles intended for uses on walls/ceilings subject to reaction to fire regulations)	
3	Emission of radioactivity (where relevant, according to material) Release of formaldehyde (where relevant, according to material) Release of asbestos (content) (only for tiles made with fibre cement) Release of other dangerous substances * (as relevant) Susceptibility to the growth of harmful micro-organisms Water vapour permeability (only for tiles intended for use on walls/ceilings subject to water vapour control requirements) Water permeability (only for tiles intended for uses on walls/ceilings subject to water penetration requirements)	
4	Shatter properties (safe breakability) (only for tiles of brittle materials intended for uses subject to requirements against accidental injuries from cutting objects) Flexural tensile strength (only for tiles intended for use in suspended ceilings) Bond strength/ adhesion (only for tiles intended for uses subject to requirements against accidental fall of objects on to transit areas)	
5	Sound absorption (only for tiles intended for acoustic conditioning)	
6	Thermal resistance / [eg density] (only for tiles intended for uses in walls/ceilings subject to thermal insulation requirements)	

* in particular, those dangerous substances defined in Council Directive 76/769/EEC, as amended.

Family and subfamilies

4.- WALL AND CEILING PANELS (except wood-based panels and plasterboards covered by previous mandates)

Elements of regular geometric forms with reduced thickness and such dimensions that can not be easily held by one person. Including fixing devises in wall panels. NB. This sub-family includes WALL CLADDING SLABS.

Characteristics of the WALL AND CEILING PANELS FOR INTERNAL USES to be covered by the harmonised standard will be:

E R	PERFORMANCE CHARACTERISTIC	Durability
1	Racking strength (only for panels intended for use as stiffening elements)	Y
2	Reaction to fire (only for panels intended for uses on walls/ceilings subject to reaction to fire regulations) Fire resistance (only for panels intended for fire protection as complete element)	
3	Emission of radioactivity (where relevant, according to material) Release of asbestos (content) (only for panels made with fibre cement) Release of formaldehyde (where relevant, according to material) Release of other dangerous substances * (as relevant) Susceptibility to the growth of harmful micro-organisms Water vapour permeability (only for panels intended for uses on walls/ceilings subject to water vapour control requirements) Water permeability (only for panels intended for uses on walls/ceilings subject to water penetration requirements)	
4	Shatter properties (Safe breakability) (only for panels of brittle materials intended for uses subject to requirements against accidental injuries from cutting objects) Flexural tensile strength (only for panels intended for use in suspended ceilings) Resistance to fixings (as relevant)	
5	Direct airborne sound insulation (in end use conditions) / [eg density] (only for panels intended for uses in walls/ceilings subject to acoustic insulation requirements) Sound absorption (only for panels intended for acoustic conditioning)	
6	Thermal resistance / [eg density] (only for panels intended for uses in walls/ceilings subject to thermal insulation requirements)	

* in particular, those dangerous substances defined in Council Directive 76/769/EEC, as amended.

5 - WALL SIDINGS

Elements of regular geometric form in which length predominates over the other two dimensions having reduced thickness. Including fixing devices where relevant.

Characteristics of the SIDINGS FOR INTERNAL USES to be covered by the harmonised standard will be:

E R	PERFORMANCE CHARACTERISTIC	Durability
1		Y
2	Reaction to fire (only for <i>sidings</i> intended for uses on walls/ceilings subject to reaction to fire regulations)	
3	Water permeability (only for <i>sidings</i> intended for uses on walls/ceilings subject to water penetration requirements) Release of asbestos (content) (only for <i>sidings</i> made with fibre cement) Release of formaldehyde (where relevant, according to material) Release of other dangerous substances * (as relevant) Susceptibility to the growth of harmful micro-organisms	
4	Shatter properties (Safe breakability) (only for <i>sidings</i> of brittle materials intended for uses subject to requirements against accidental injuries from cutting objects) Resistance to fixings (only <i>sidings with associated fixings</i> intended for uses subject to requirements against accidental fall of objects on to transit areas) Bond strength/Adhesion (only for <i>sidings</i> intended for uses subject to requirements against accidental fall of objects on to transit areas)	
5		
6	Thermal resistance/[eg density] (only for <i>sidings</i> intended for uses in walls/ceilings subject to thermal insulation requirements)	

* in particular, those dangerous substances defined in Council Directive 76/769/EEC, as amended.

Subfamily

6.- ANCILLARY PRODUCTS FOR INTERNAL FINISHES IN WALLS AND CEILING (except those for wood-based panels and plasterboards presented in the relevant mandates)

6 A.-FEATURED PROFILES ¹

Profiles intended for supporting internal wall and ceiling finishes.

6 B.-SUSPENDING FRAMES ²

Kits of sections used to form the supporting structure for suspended ceilings where the panels may or may not conceal the frame

Characteristics of ANCILLARY PRODUCTS FOR INTERNAL FINISHES IN WALLS AND CEILINGS to be covered by the harmonised standard will be:

E R	PERFORMANCE CHARACTERISTIC	Durability
1		Y
2	Reaction to fire (for <i>feature profiles and suspending frames</i> intended for use in situations exposed to fire on walls/ceilings subject to reaction to fire regulations)	
3		
4	Load bearing capacity (only for <i>suspending frames</i> in suspended ceilings) Resistance to fixings (as relevant for <i>profiles/ frames with associated fixings</i>)	
5		
6		

¹ Only profiles not covered by previous mandates.

² Only suspending frames not covered by previous mandates.

7 - SUSPENDED CEILINGS (kits)

Composed of ceiling tiles or panels and relevant suspending frame.

Characteristics of the SUSPENDED CEILINGS FOR INTERNAL USES to be covered by the harmonised standard will be:

E R	PERFORMANCE CHARACTERISTIC	Durability
1		
2	Reaction to fire (<i>only for suspended ceilings intended for uses subject to reaction to fire regulations</i>) Fire resistance (<i>only for suspended ceilings intended for fire protection</i>)	Y
3	Emission of radioactivity (<i>where relevant, according to material</i>) Release of asbestos (content) (<i>only for suspended ceilings with tiles or panels of fibre cement</i>) Release of formaldehyde (<i>where relevant, according to material</i>) Release of other dangerous substances * (<i>as relevant</i>) Susceptibility to the growth of harmful micro-organisms Water permeability (<i>only for suspended ceilings intended for uses on ceilings subject to water penetration requirements</i>)	
4	Shatter properties (Safe breakability) (<i>only for suspended ceilings with tiles or panels of brittle materials intended for uses subject to requirements against accidental injuries from cutting objects</i>) Flexural tensile strength (<i>only for the panels or tiles of the kit</i>) Load bearing capacity (<i>only for the suspending frames of the kit</i>) Resistance to fixings (<i>as relevant for kits with associated fixings</i>)	
5	Direct airborne sound insulation (<i>in end use conditions</i>) / [eg density] (<i>only for suspended ceilings intended for uses in ceilings subject to acoustic insulation requirements</i>) Sound absorption (<i>only for suspended ceilings intended for uses subject to acoustic conditioning requirements</i>)	
6	Thermal resistance / [eg density] (<i>only for suspended ceilings intended for uses in ceilings subject to thermal insulation requirements</i>)	

* in particular, those dangerous substances defined in Council Directive 76/769/EEC, as amended.

Family

EXTERNAL FINISHES

Subfamilies

8.- WALL AND CEILING³ TILES

Elements of regular geometric forms with reduced thickness and such dimensions that can be easily held by one person. To be adhered or mechanically fixed to wall or ceiling or suspended to ceiling.

9.- WALL CLADDING SLABS

Heavy duty elements of regular geometric forms with reduced thickness and medium size dimensions that can not be easily held by one person. Including fixing devices.

10.- WALL SHINGLES

Elements of regular geometric forms with very reduced thickness and such dimensions that can be easily held by one person. To be installed overlapping. Including fixing devices

11.- WALL SIDINGS

Elements of regular geometric form in which length predominates over the other two dimensions having reduced thickness. Including fixing devices where relevant.

Characteristics of the WALL AND CEILING TILES, CLADDING SLABS, SHINGLES AND SIDINGS FOR EXTERNAL USES to be covered by the harmonised standard will be:

E R	PERFORMANCE CHARACTERISTIC	Durability
1		
2	Reaction to fire (only for <i>tiles, cladding slabs, shingles and sidings</i> intended for uses on walls/ceilings subject to reaction to reaction to fire regulations)	
3	Water vapour permeability (only for <i>tiles and cladding slabs</i> intended for use on walls/ceilings subject to water vapour control requirements) Water permeability (only for <i>tiles, cladding slabs, shingles and sidings</i> intended for uses on walls/ceilings subject to water penetration requirements) Release of asbestos (content) (only for <i>tiles, cladding slabs, shingles and sidings of fibre cement</i>) Release of other dangerous substances * (as relevant)	Y (Against
4	Shatter properties (Safe breakability) (only for <i>tiles, cladding slabs, shingles and sidings</i> of brittle materials intended for uses subject to requirements against accidental injuries from cutting objects) Mechanical resistance (e.g. flexural tensile strength, ..., as relevant for slabs) Resistance to fixings (only for <i>cladding slabs, shingles and sidings with associated fixings</i> intended for uses subject to requirements against accidental fall of objects onto transit areas) Bond strength/Adhesion (only for <i>tiles</i> intended for uses subject to requirements against accidental fall of objects on to transit areas(see note below) Thermal shock resistance (where relevant, according to material)	weathering, freeze-thaw, de-icing salts, ...as relevant)
5	Direct airborne sound insulation (in end use conditions) / [eg density] (only for <i>cladding slabs</i> intended for uses in walls/ceilings subject to acoustic insulation requirements)	
6	Thermal resistance/[eg density] (only for <i>cladding slabs and sidings</i> intended for uses in walls/ceilings subject to thermal insulation requirements)	

* in particular, those dangerous substances defined in Council Directive 76/769/EEC, as amended.

³ The term “external ceilings” refers to ceilings in non enclosed and semi-enclosed spaces (e.g. terrace ceiling). In some situations these external surfaces are called soffits.

Subfamilies

12.- WALL AND CEILING PANELS (except wood-based panels and plasterboards as presented in previous mandates)

Elements of regular geometric forms with reduced thickness and such dimensions that can not be easily held by one person, including large metallic claddings, high/low pressure laminates and sandwich panels. Including fixing devices in wall panels.

Characteristics of WALL AND CEILING PANELS FOR EXTERNAL USES to be covered by the harmonised standard will be:

E R	PERFORMANCE CHARACTERISTIC	Durability
1	Racking strength (only for panels intended for use as stiffening elements)	<p align="center">Y</p> <p align="center">(Against weathering, freeze-thaw, de-icing salts, ... as relevant)</p>
2	Fire resistance (in end use conditions) (only for panels intended for fire protection of walls/ceilings as complete elements) Reaction to fire (only for panels intended for use on walls/ceilings subject to reaction to fire regulations)	
3	Water vapour permeability (only for panels intended for use on walls/ceilings subject to water vapour control requirements) Water permeability (only for panels intended for uses on walls/ceilings subject to water penetration requirements) Release of asbestos (content) (only for panels of fibre cement) Release of other dangerous substances * (as relevant)	
4	Shatter properties (Safe breakability) (only for panels of brittle materials intended for uses subject to requirements against accidental injuries from cutting objects and against accidental fall of objects on to transit areas) Resistance to fixings (only for panels intended for uses subject to requirements against accidental fall of objects on to transit areas) Thermal shock resistance (where relevant, according to material) Flexural tensile strength (including resistance to wind load) (for panels intended for suspended ceilings)	
5	Direct airborne sound insulation (in end use conditions) / [eg density] (only for panels intended for uses in walls/ceilings subject to acoustic insulation requirements)	
6	Thermal resistance/[eg density] (only for panels intended for uses in walls/ceilings subject to thermal insulation requirements)	

* in particular, those dangerous substances defined in Council Directive 76/769/EEC, as amended.

Subfamily

13.- ANCILLARY PRODUCTS FOR EXTERNAL FINISHES IN WALLS AND CEILINGS (except those for wood-based panels and plasterboards presented in the relevant mandates)

13 A.-FEATURED PROFILES ⁴

Profiles intended for supporting external wall and ceiling finishes.

13 B.-SUSPENDING FRAMES ⁵

Kits of sections used to form the supporting structure for suspended ceilings where the panels may or may not conceal the frame

Characteristics of the ANCILLARY PRODUCTS FOR EXTERNAL FINISHES IN WALLS AND CEILINGS to be covered by the harmonised standard will be:

E R	PERFORMANCE CHARACTERISTIC	Durability
1		Y (Against UV,..., as relevant)
2	Reaction to fire (for <i>feature profiles and suspending frames</i> intended for use in situations exposed to fire on walls/ceilings subject to fire regulations)	
3		
4	Load bearing capacity (only for <i>suspending frames</i> in suspended ceilings) Resistance to fixings (as relevant for <i>profiles/ frames with associated fixings</i>)	
5		
6		

14 - SUSPENDED CEILINGS (kits)

Composed of ceiling tiles or panels and relevant suspending frame.

Characteristics of the SUSPENDED CEILINGS FOR EXTERNAL USES to be covered by the harmonised standard will be:

E R	PERFORMANCE CHARACTERISTIC	Durability
1		Y
2	Reaction to fire (only for <i>suspended ceilings</i> intended for uses subject to reaction to fire regulations) Fire resistance (only for <i>suspended ceilings</i> intended for fire protection)	
3	Emission of radioactivity (where relevant, according to material) Release of asbestos (content) (only for <i>suspended ceilings</i> with tiles or panels of fibre cement) Release of other dangerous substances * (as relevant) Water permeability (only for <i>suspended ceilings</i> intended for uses on ceilings subject to water penetration requirements)	
4	Shatter properties (Safe breakability) (only for <i>suspended ceilings</i> with tiles or panels of brittle materials intended for uses subject to requirements against accidental injuries from cutting objects) Flexural tensile strength (only for <i>the panels</i> or tiles of the kit) Load bearing capacity (only for <i>the suspending frames of the kit</i>) Resistance to fixings (as relevant for <i>kits with associated fixings</i>)	
5	Direct airborne sound insulation (in end use conditions) / [eg density] (only for <i>suspended ceilings</i> intended for uses in walls/ceilings subject to acoustic insulation requirements))	
6	Thermal resistance / [eg density] (only for <i>suspended ceilings</i> intended for uses in walls/ceilings subject to thermal insulation requirements)	

* in particular, those dangerous substances defined in Council Directive 76/769/EEC, as amended.

⁴ Only plastic profiles as the metallic and timber ones have already been the subject of other mandates.

⁵ Only suspending frames not covered in previous mandates.

ANNEX 3
ATTESTATION OF CONFORMITY

Note : for products having more than one of the intended uses specified in the following families, the tasks for the approved body, derived from the relevant systems of attestation of conformity, are cumulative.

Product family : INTERNAL AND EXTERNAL WALL AND CEILING FINISHES (1/5)

1. Levels and classes for product performances

1.1 According to article 3.2 of the CPD and Clause 1.2.1 of the IDs, a classification of product performance has been identified as the means of expressing the range of requirement levels of the works in respect of **resistance to fire**.

CEN/CENELEC is requested to make reference to the standard(s) to be prepared under Commission mandate to CEN/CENELEC "Horizontal complement to the mandates in respect of resistance to fire" in dealing with resistance to fire in the specific HARMONISED STANDARDS to be developed under this mandate.

1.2 Reaction to fire and resistance to fire are risks for which the need for a classification has been identified for the time being.

Further needs may be identified on the basis of differences specified in Article 3 (2) of the CPD, which are justified in conformity with Community law (IDs Clause 1.2.1).

Where for such needs it is recognised that a classification of product performance is the means of expressing the range of requirement levels of the works, the Commission will give the appropriate guidance or will request CEN/CENELEC to make the appropriate proposal through a modification to this mandate.

2. Systems of attestation of conformity

For the product(s) and intended use(s) listed below, CEN/CENELEC are requested to specify the following system(s) of attestation of conformity in the relevant harmonised standard(s) :

Product(s)	Intended use(s)	Level(s) or class(es) <i>(fire resistance)</i>	Attestation of conformity system(s)
Panels	as internal or external finishes, as complete elements, used for fire protection of walls or ceilings	any	3
Suspended ceilings (kits)	as internal or external finishes used for fire protection of ceilings		
System 3: See CPD Annex III.2.(ii), Second possibility			

3. Conditions to be applied by CEN on the specifications of the attestation of conformity system

3.1 The specification for the system should be such that it can be implemented even where performance does not need to be determined for a certain characteristic, because at least one Member State has no legal requirement at all for such characteristic [see Article 2.1 of the CPD and, where applicable, clause 1.2.3 of the Interpretative Documents]. In those cases the verification of such a characteristic must not be imposed on the manufacturer if he does not wish to declare the performance of the product in that respect.

3.2 For products under system 3, regarding the initial type testing of the product (to be required by the manufacturer in case of system 3) [see Annex III.1.a) of the CPD], the task for the approved laboratory will be limited to the assessment of the following characteristics:

- **Fire resistance**

Product family : **INTERNAL AND EXTERNAL WALL AND CEILING FINISHES (2/5)**

1. Levels and classes for product performances

- 1.1 For the time being, the differences specified in Article 3 (2) of the CPD, do not seem to give rise to the need of a classification system for products for other characteristics than **reaction to fire** and **fire resistance**.
- 1.2 Further needs may be identified on the basis of differences specified in Article 3 (2) of the CPD, which are justified in conformity with Community law (IDs Clause 1.2.1). Where for such needs it is recognised that a classification of product performance is the means of expressing the range of requirement levels of the works, the Commission will give the appropriate guidance or will request CEN/CENELEC to make the appropriate proposal through a modification to this mandate.

2. Systems of attestation of conformity

For the product(s) and intended use(s) listed below, CEN/CENELEC are requested to specify the following system(s) of attestation of conformity in the relevant harmonised standard(s) :

Product(s)	Intended use(s)	Level(s) or class(es) <i>(Reaction to fire)</i>	Attestation of conformity system(s)
Panels	as internal or external stiffening elements in walls or ceilings	---	3
Tiles Panels <i>(of brittle materials)</i>	as internal or external finishes in walls or ceilings subject to requirements against accidental injuries from cutting objects		
Suspended ceilings (kits)	as internal or external finish in ceilings subject to safety in use requirements		
Tiles Panels	in internal or external suspended ceilings subject to safety in use requirements		
Featured profiles Suspending frames	to support internal or external wall or ceiling finishes and suspended ceilings subject to safety in use requirements		
System 3: See CPD Annex III.2.(ii), Second possibility			

3. Conditions to be applied by CEN on the specifications of the attestation of conformity system

- 3.1 The specification for the system should be such that it can be implemented even where performance does not need to be determined for a certain characteristic, because at least one Member State has no legal requirement at all for such characteristic [see Article 2.1 of the CPD and, where applicable, clause 1.2.3 of the Interpretative Documents]. In those cases the verification of such a characteristic must not be imposed on the manufacturer if he does not wish to declare the performance of the product in that respect.
- 3.2 For products under system 3, regarding the initial type testing of the product (to be required by the manufacturer in case of system 3) [see Annex III.1.a) of the CPD], the task for the approved laboratory will be limited to the assessment of the following characteristics:

For panels with stiffening function:

- **Racking strength**

For featured profiles and suspending frames:

- **Load-bearing capacity**

For panels and tiles of brittle materials in walls or ceilings subject to requirements against accidental injuries from cutting objects:

- **Shatter properties (safe breakability)**

For panels and tiles for suspended ceiling:

- **Flexural tensile strength**

For suspended ceilings (kits):

- **Flexural tensile strength** (of panels or tiles)
- **Load-bearing capacity** (of suspended frames)

1. Levels and classes for product performances

- 1.1 According to article 3.2 of the CPD and Clause 1.2.1 of the IDs, a classification of product performance has been identified as the means of expressing the range of requirement levels of the works in respect of **Reaction to fire**. CEN/CENELEC are requested to follow the Commission Decision 94/611/EC [O.J. L 241 of September 1994] and make reference to the standard(s) to be prepared under Commission mandate "Horizontal complement to the 33 mandates in respect of reaction to fire" in dealing with reaction to fire in the specific harmonised product standards to be developed under this mandate.
- 1.2 Reaction to fire is one performance characteristic for which the need for a classification system for products has been identified for the time being.

Further needs may be identified on the basis of differences specified in Article 3 (2) of the CPD, which are justified in conformity with Community law (IDs Clause 1.2.1). Where for such needs it is recognised that a classification of product performance is the means of expressing the range of requirement levels of the works, the Commission will give the appropriate guidance or will request CEN/CENELEC to make the appropriate proposal through a modification to this mandate.

2. Systems of attestation of conformity

For the product(s) and intended use(s) listed below, CEN/CENELEC are requested to specify the following system(s) of attestation of conformity in the relevant harmonised standard(s) :

Product(s)	Intended use(s)	Level(s) or class(es) <i>(Reaction to fire)</i> ⁶	Attestation of conformity system(s)
Coverings in roll form Linings	as internal finishes in walls or ceilings subject to reaction to fire regulations	A ^(*) , B ^(*) and C ^(*)	1
Shingles Cladding slabs	as external finishes in walls or ceilings subject to reaction to fire regulations	A ^(**) , B ^(**) and C ^(**)	3
Suspended ceilings (kits)	as internal or external finish in ceilings subject to reaction to fire regulations		
Tiles Sidings Panels	as internal or external finishes in walls or ceilings subject to reaction to fire regulations	A (without testing), D, E and F	4
Featured profiles Suspending frames	to support internal or external wall or ceiling finishes, or suspended ceilings, subject to reaction to fire regulations		
System 1: See CPD Annex III.2.(i), without audit-testing of samples System 3: See CPD Annex III.2.(ii), Second possibility System 4: See CPD Annex III.2.(ii), Third possibility			

⁶ For reaction to fire, see Commission Decision 94/611/EC

(*) Materials for which the reaction to fire performance is susceptible to change during the production process

(**) Materials for which the reaction to fire performance is not susceptible to change during the production process

3. Conditions to be applied by CEN on the specifications of the attestation of conformity system

- 3.1 The specification for the system should be such that it can be implemented even where performance does not need to be determined for a certain characteristic, because at least one Member State has no legal requirement at all for such characteristic [*see Article 2.1 of the CPD and, where applicable, clause 1.2.3 of the Interpretative Documents*]. In those cases the verification of such a characteristic must not be imposed on the manufacturer if he does not wish to declare the performance of the product in that respect.
- 3.2 For products under systems 1 and 3, regarding the initial type testing of the product (to be required by the manufacturer in case of system 3) [see Annex III.1.a) of the CPD], the task for the approved laboratory will be limited to the assessment of the following characteristics:
 - **Euroclass characteristics for reaction to fire**, as indicated in the Commission Decision 94/611/EC
- 3.3 For products under system 1, for the continuous surveillance, assessment and approval of the factory production control [see Annex III.1.g) of the CPD], only parameters related to the following characteristics shall be of the interest of the approved body:
 - **Euroclass characteristics for reaction to fire**, as indicated in the Commission Decision 94/611/EC
- 3.5 For products under systems 1, for the initial inspection of the factory and of the factory production control [see Annex III.1.f) of the CPD], only parameters related to the following characteristics shall be of the interest of the approved body.
 - **Euroclass characteristics for reaction to fire**, as indicated in the Commission Decision 94/611/EC

1. Levels and classes for product performances

- 1.1 For the time being, the differences specified in Article 3 (2) of the CPD, do not seem to give rise to the need of a classification system for products for other characteristics than **reaction to fire** and **fire resistance**.
- 1.2 Further needs may be identified on the basis of differences specified in Article 3 (2) of the CPD, which are justified in conformity with Community law (IDs Clause 1.2.1). Where for such needs it is recognised that a classification of product performance is the means of expressing the range of requirement levels of the works, the Commission will give the appropriate guidance or will request CEN/CENELEC to make the appropriate proposal through a modification to this mandate.

2. Systems of attestation of conformity

For the product(s) and intended use(s) listed below, CEN/CENELEC are requested to specify the following system(s) of attestation of conformity in the relevant harmonised standard(s) :

Product(s)	Intended use(s)	Level(s) or class(es)	Attestation of conformity system(s)
Suspended ceilings (kits)	as internal or external finishes in walls or ceilings subject to regulations on dangerous substances *		
Tiles Shingles Sidings Cladding slabs Panels	as internal or external finishes in walls or ceilings, as relevant, subject to regulations on dangerous substances *	-	3
System 3: See CPD Annex III.2.(ii), Second possibility			

* in particular, those dangerous substances defined in Council Directive 76/769/EEC, as amended.

3. Conditions to be applied by CEN on the specifications of the attestation of conformity system

- 3.1 The specification for the system should be such that it can be implemented even where performance does not need to be determined for a certain characteristic, because at least one Member State has no legal requirement at all for such characteristic [see Article 2.1 of the CPD and, where applicable, clause 1.2.3 of the Interpretative Documents]. In those cases the verification of such a characteristic must not be imposed on the manufacturer if he does not wish to declare the performance of the product in that respect.
- 3.2 For products under system 3, regarding the initial type testing of the product (to be required by the manufacturer in case of system 3) [see Annex III.1.a) of the CPD], the task for the approved laboratory will be limited to the assessment of the following characteristics:

- Release of dangerous substances * (content)

1. Levels and classes for product performances

- 1.1 For the time being, the differences specified in Article 3 (2) of the CPD, do not seem to give rise to the need of a classification system for products for other characteristics than **reaction to fire** and **fire resistance**.
- 1.2 Further needs may be identified on the basis of differences specified in Article 3 (2) of the CPD, which are justified in conformity with Community law (IDs Clause 1.2.1). Where for such needs it is recognised that a classification of product performance is the means of expressing the range of requirement levels of the works, the Commission will give the appropriate guidance or will request CEN/CENELEC to make the appropriate proposal through a modification to this mandate.

2. Systems of attestation of conformity

For the product(s) and intended use(s) listed below, CEN/CENELEC are requested to specify the following system(s) of attestation of conformity in the relevant harmonised standard(s) :

Product(s)	Intended use(s)	Level(s) or class(es) (<i>Reaction to fire</i>)	Attestation of conformity system(s)
Suspended ceilings (kits)	as internal or external finish in ceilings for other uses mentioned in the mandate ⁷		
Wall coverings in roll form Ceiling linings Tiles Shingles Sidings Cladding slabs Panels	as internal or external finishes in walls or ceilings for other uses mentioned in the mandate ¹¹	---	4
Featured profiles Suspending frames	to support internal or external wall or ceiling finishes, or suspended ceilings, for other uses mentioned in the mandate ¹¹		
System 4: See CPD Annex III.2.(ii), Third possibility			

3. Conditions to be applied by CEN on the specifications of the attestation of conformity system

- 3.1 The specification for the system should be such that it can be implemented even where performance does not need to be determined for a certain characteristic, because at least one Member State has no legal requirement at all for such characteristic [see *Article 2.1 of the CPD and, where applicable, clause 1.2.3 of the Interpretative Documents*]. In those cases the verification of such a characteristic must not be imposed on the manufacturer if he does not wish to declare the performance of the product in that respect.

⁷ Other intended uses covered by the mandate are: for vapour control, for water penetration control; for acoustic control; and for thermal control

ANNEX 4
DANGEROUS SUBSTANCES

INTERNAL AND EXTERNAL WALL AND CEILING FINISHES

European technical specifications must be adopted taking into account necessary legislation on substances classified as dangerous.

This results from the Interpretative Documents, where it is noted, in the introduction note to all six of them, that:

"Concerning dangerous substances which are in construction products, classes and/or levels of performance to which technical specifications will refer, shall allow the levels of protection needed by the works to be guaranteed, taking into account the purpose of the works."

In addition, outside the scope of the Directive, writers of technical specifications must take into account legislation which affects materials to be used for construction products and which are regulated for reasons not related to the incorporation of the construction products into the works.

In order to permit technical specifications writers to take into account the necessary legislation, a working document was elaborated by the Commission services (doc. CONSTRUCT 95/148 Rev. 1 of January 4, 1996). Specification writers should use this document as a guide but must also take account of any other relevant or dangerous substances which the working document does not yet include.